

Green Lawnger®

Turf Colourant

Naturally green turf that won't wash off

- Natural restoration of green turf colour with a pigment, not a dye, prolonging the healthy appearance of turf
- Long lasting, natural green colour which lasts up to four months (120+ days) after a single application
- A durable colour that won't fade to blue even under prolonged UV exposure
- Replacing expensive over-seeding programs, Green Lawnger is efficient and cost effective in extending turf use into the cooler months.
- Suitable for use in the pre-treatment of divot mix sand to optimise blending with treated turf

For more information on Green Lawnger®, visit turf-solutions.basf.com.au or contact your local BASF representative on **1800 558 399**

■ - BASF
We create chemistry

Green Lawngr®

Turf Colourant

Green Lawngr® is an efficient turf paint and divot mix colourant which adds a healthy appearance to warm – and cool – season turf grasses. This innovative, natural pigment will not wash off or wear on turf, restoring the green colour for up to four months (120+ days) after a single application. Green Lawngr replaces expensive over-seeding programs, offering a cost effective, efficient and natural solution to extend golf play into the cooler months of winter. Not only is Green Lawngr non-phytotoxic to turf, it can also be pre-applied to divot mix sand for optimum blending with turf. Green Lawngr is the perfect solution to naturally green turf, all year round.

Directions for use	<p>Before applying Green Lawngr®, mow turf area to desired height. 1L of Green Lawngr covers between 100 and 300m² of turf. The wide coverage range is due to the type of condition of grass being treated, and turf colour desired. For fall application on dormant turf, dilute 1L of Green Lawngr® with 7 to 9 L of water. For a darker colour, a lower volume of water is recommended. Some experimentation may be required with ratios.</p> <p>For summer application on discoloured turf, dilute 1L with 15 to 20 L of water. Rate depends on desired colour. For best results on discoloured areas, two applications are recommended to blend the applied area with the existing healthy turf.</p>
Equipment notice	<p>BASF recommends the use of Teflon seals to aid in the prevention of leaks when using Green Lawngr® in centrifugal pumps. Standard ceramic seals may leak during operation. A spray shield is recommended for application if overspray or drift is a potential problem. Avoid overspray on concrete, masonry, or any other objects where colour is not desired. Permanent staining may occur. Accidental overspray may be removed by a water rinse prior to drying. To prevent ruboff on uniforms, allow Green Lawngr to dry prior to using athletic field. Rinse spray tank, spray nozzles, and screens thoroughly with water immediately following use. For best results, use low to medium sprayer pressure.</p> <p>DIVOT MIX SAND Mix 200mL of Green Lawngr with the same volume of water. Spray or pour the solution onto 50kg of divot mix sand in a cement-type mixer.</p>

Refer to the product label for full directions for use table.

Packaging

Available in 10L Bottles



For more information on Green Lawngr®, visit turf-solutions.basf.com.au or contact your local BASF representative on **1800 558 399**

ALWAYS READ AND FOLLOW LABEL DIRECTIONS BEFORE USING ANY PRODUCT IN THIS FACT SHEET.

This fact sheet is intended as general advice. Disclaimer: The information submitted in this publication is based on current BASF knowledge and experience. In view of the many factors that may affect its application, this data does not relieve the user from carrying out their own tests. The data does not imply assurance of certain properties or of suitability for a specific purpose. It is the responsibility of the user to ensure that any proprietary rights and existing laws and legislation are observed.